

INDUSTRIAL COMPONENT DATA

PKE-XHT-MCC 164299 Y7-164299 EATON ELECTRIC Door coupling handle, for MCC-V, 90 degree, twisted

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XHT-MCC



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XHT-MCC
Catalog number	Y7-164299
Category	Door coupling handle for switchgear
Minimum order	1 Pcs
Document ID	EO-5B0CB26BD2
Generated	2026-08-05

Product Overview

Door coupling handle, for MCC-V, 90 degree, twisted

PKE-XHT-MCC

Eaton Moeller® series PKE Door coupling handle, for MCC-V, 90 degree, twisted

For use as a main switch to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90°

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Door coupling handle Catalog Number 164299 Model Code PKE-XHT-MCC
EAN 4015081608270 Product Length/Depth 235 mm Product Height 66 mm Product Width 64 mm Product Weight 0.16 kg

Certifications EN 60204 Catalog Notes Cannot be used in combination with VHI20-PKZ0. Features & Functions

Color Black Features Lockable Fitted with: Door interlock

3 padlocks, 4 - 8 mm hasp thickness

ON/OFF switch position and "+" (tripped), lockable

Axis extension General

Degree of protection IP65

NEMA Other Product Category Accessories Suitable as Main switch to EN 60204 in MCC power distribution systems and with PKE installed when rotated by 90° Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XHT-MCC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.