

## INDUSTRIAL COMPONENT DATA

# PKE-XRHT-MCC 164350 Y7-164350 EATON ELECTRIC Door coupling handle, for MCC, 90 degree, NA type

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XRHT-MCC



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | PKE-XRHT-MCC                        |
| Catalog number  | Y7-164350                           |
| Category        | Door coupling handle for switchgear |
| Minimum order   | 1 Pcs                               |
| Document ID     | EO-D1A0C10697                       |
| Generated       | 2026-08-05                          |

## Product Overview

Door coupling handle, for MCC, 90 degree, NA type

PKE-XRHT-MCC

Eaton Moeller® series PKE Door coupling handle, for MCC, 90 degree, NA type

Door coupling handle with NA radio, MCC 90 degree, for use as a main switch with emergency switching off function to EN 60204 in MCC power distribution systems and with PKZM90 installed when rotated by 0°

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

## Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Door coupling handle Catalog Number 164350 Model Code PKE-XRHT-MCC  
EAN 4015081608287 Product Length/Depth 235 mm Product Height 66 mm Product Width 64 mm Product Weight 0.16 kg  
Certifications EN 60204 Catalog Notes Cannot be used in combination with VHI20-PKZ0. Features & Functions

Color Yellow

Red Features Lockable Fitted with: ON/OFF switch position and "+" (tripped), lockable

Handle red/yellow

3 padlocks, 4 - 8 mm hasp thickness

Door interlock

Axis extension General

Degree of protection IP65

NEMA Other Product Category Accessories Suitable as Main switch with Emergency-Stop function to EN 60204 in MCC power distribution systems and with PKE installed when rotated by 90° Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification Equipment heat dissipation, current-dependent P<sub>vid</sub> 0 W Heat dissipation capacity P<sub>diss</sub> 0 W Heat dissipation per pole, current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by inte...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XRHT-MCC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.