

INDUSTRIAL COMPONENT DATA

PKE-XTU-36 171497 XTPEXT036B EATON ELECTRIC Trip block, 8-36 A, standard, motor protection

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XTU-36



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XTU-36
Catalog number	Y7-171497
Category	Tripping bloc for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-F0D1E94E05
Generated	2026-08-05

Product Overview

Trip block, 8-36 A, standard, motor protection

PKE-XTU-36

Trip block, Motor protection, Connection to SmartWire-DT: no, For use with: PKE32 basic device

Electronic control unit for motor protection according to IEC60947-4-1 for basic device PKE32, electronic wide-range overload protection (4:1), phase-failure and unbalance protection, adjustable tripping class. ATEX accreditation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Trip block Catalog Number 171497 Model Code PKE-XTU-36 EAN

4015081679850 Product Length/Depth 41.6 mm Product Height 64.2 mm Product Width 45 mm Product Weight 0.09 kg

Certifications IEC/EN 60947

VDE 0660 Catalog Notes Features & Functions

Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Functions Short-circuit protection Motor protection

Overcurrent protection Number of poles Three-pole General

Current flow times - min For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

700 (Class 10) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

1000 (Class 20) AC-4 cycle operation, Main conducting paths

500 (Class 5) AC-4 cycle operation, Main conducting paths Cut-out periods - min $\leq$ 500 ms, main conducting paths, AC-4 cycle operation Degree of protection Device: IP20

Terminals: IP00 Operating frequency 60 Operations/h Overload release current setting - min 8 A Overload release current setting - max 36 A Overvoltage category III Pollution degree 3 Product category Accessories Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Temperature compensation -25 - 55 °C,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XTU-36 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.