

INDUSTRIAL COMPONENT DATA

PKE-XTUWCP-36 168796 Y7-168796 EATON ELECTRIC Trip block, 3p, 15-36A, system protection, standard

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XTUWCP-36



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XTUWCP-36
Catalog number	Y7-168796
Category	Tripping bloc for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-F2BA11C7CD
Generated	2026-08-05

Product Overview

Trip block, 3p, 15-36A, system protection, standard

PKE-XTUWCP-36

Eaton Moeller® series PKE Trip block, 15 - 36 A, System protection, Connection to SmartWire-DT: no, For use with: PKE65 basic device

Electronic control unit for system protection as per IEC 60947-2, mounting without tools with PKE65 basic device, adjustable electronic wide-range overload protection (2, 4 : 1), adjustable short-circuit releases

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Electronic Circuit Breakers**

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Trip block Catalog Number 168796 Model Code PKE-XTUWCP-36 EAN 4015081652877 Product Length/Depth 84.4 mm Product Height 69.9 mm Product Width 55 mm Product Weight 0.196 kg Certifications VDE 0660

IEC/EN 60947 Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features &

Functions

Functions Line and cable protection

System protection

Short-circuit protection

Overcurrent protection Number of poles Three-pole General

Current flow times - min Note: Going below the minimum current flow time can cause overheating of the load (motor).

500 (Class 5) AC-4 cycle operation, Main conducting paths

700 (Class 10) AC-4 cycle operation, Main conducting paths

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

1000 (Class 20) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle operation Degree of protection Terminals: IP00

Device: IP20 Operating frequency 60 Operations/h Overload release current setting - min 15 A Overload release current setting - max 36 A Overvoltage category III Pollution degree 3 Product category Accessories Protection Finger and back-of-hand proof, Protection....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XTUWCP-36 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.