

INDUSTRIAL COMPONENT DATA

PKE-XZMR(230V50HZ) 173416 Y7-173416 EATON ELECTRIC

Overload relay function, 230 V 50Hz

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XZMR(230V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XZMR(230V50HZ)
Catalog number	Y7-173416
Category	Electronic overload relay
Minimum order	1 Pcs
Document ID	EO-F15287D5AA
Generated	2026-08-05

Product Overview

Overload relay function, 230 V 50Hz

PKE-XZMR(230V50HZ)

Eaton Moeller® series PKE Overload relay function, 230 V 50Hz

Overload relay module, For use with: PKE12, PKE32, PKE65 with XTUA trip block with release 04 and higher

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Overload relay module Catalog Number 173416 Model Code

PKE-XZMR(230V50HZ) EAN 4015081698172 Product Length/Depth 105 mm Product Height 50 mm Product Width 105 mm Product Weight 0.079 kg Compliances CE Features & Functions

Features Status display via LED Functions Adjustable manual/auto reset

Overload relay function (the motor-protective circuit-breaker will not trip in the event of an overload) General

Class Other Lifespan, electrical 200,000 Operations Lifespan, mechanical 5,000,000 Operations Mounting method Direct attachment Overvoltage category III Pollution degree 3 Product Category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Voltage type AC Ambient conditions, mechanical

Mounting position Right side (of PKE motor-protective circuit-breakers with advanced PKE-XTU...A... trip blocks) Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 2.5 mm² Terminal capacity (solid/stranded AWG) 18 - 14 Electrical rating
Operational voltage 0.8 - 1.1 x U_s (alternating voltage) Rated operational current (I_e) at AC-15, 220 V, 230 V, 240 V 1.5 A
Rated operational voltage (U_e) at AC - max 500 V Safe isolation 440 V, Between auxiliary contacts and main contacts,
According to EN 61140 Safe isolation 440 V, Between auxiliary contacts and main contacts, According to EN 61140 Short...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XZMR(230V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.