

INDUSTRIAL COMPONENT DATA

PKE-XZMR(24VDC) 173425 Y7-173425 EATON ELECTRIC

Electronic control relay, rated operating voltage 24VDC, 8 d..

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XZMR(24VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XZMR(24VDC)
Catalog number	Y7-173425
Category	Electronic overload relay
Minimum order	1 Pcs
Document ID	EO-2F6A420C9B
Generated	2026-08-01

Product Overview

Electronic control relay, rated operating voltage 24VDC, 8 digital inputs 24VDC, 2 inputs can be used as analog inputs, 4 relay outputs, keyboard, LCD display, time switch, menu also available in Cyrillic
PKE-XZMR(24VDC)

Eaton Moeller® series PKE Overload relay function, 24 V DC

Overload relay module, For use with: PKE12, PKE32, PKE65 with XTUA trip block with release 04 and higher

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Overload relay module Catalog Number 173425 Model Code

PKE-XZMR(24VDC) EAN 4015081698288 Product Length/Depth 105 mm Product Height 50 mm Product Width 105 mm

Product Weight 0.079 kg Compliances CE Features & Functions

Features Status display via LED Functions Adjustable manual/auto reset

Overload relay function (the motor-protective circuit-breaker will not trip in the event of an overload) General

Class Other Lifespan, electrical 200,000 Operations Lifespan, mechanical 5,000,000 Operations Mounting method Direct attachment Overvoltage category III Pollution degree 3 Product Category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Voltage type DC Ambient conditions, mechanical

Mounting position Right side (of PKE motor-protective circuit-breakers with advanced PKE-XTU...A... trip blocks) Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities
Terminal capacity (solid/flexible with ferrule) 0.75 - 2.5 mm² Terminal capacity (solid/stranded AWG) 18 - 14 Electrical rating
Operational voltage 0.8 - 1.1 x Us Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 7777777 A Rated
operational voltage (Ue) at AC - max 7777777 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation 440 V,
Between auxiliary contacts and main contacts, According to EN 61140 Safe isolation 440 V, Between auxiliary contacts and
main conta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XZMR(24VDC) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.