

INDUSTRIAL COMPONENT DATA

PKE12/AK/XTU-12 158243 Y7-158243 EATON ELECTRIC

Motor-protective circuit-breaker, 3p, +control option 3-12A

Brand: EATON - MOELLER | Manufacturer Part Number: PKE12/AK/XTU-12



Manufacturer	EATON - MOELLER
MPN / Reference	PKE12/AK/XTU-12
Catalog number	Y7-158243
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-5756C71B94
Generated	2026-08-06

Product Overview

Motor-protective circuit-breaker, 3p, +control option 3-12A

PKE12/AK/XTU-12

Eaton Moeller® series PKE12 Motor-protective circuit-breaker, Complete device with AK lockable rotary handle, Electronic, 3 - 12 A, With overload release

Motor-protective circuit-breaker complete device (basic device and electronic control unit) according to IEC60947-4-1, electronic wide-range overload protection (4:1), phase-failure and unbalance protection, adjustable tripping class, high short-circuit breaking capacity, isolating function, lockable in the 0 (Off) position . Flexible adaptation of the motor-protective circuit's current range through interchangeable.electronic release units. Expandable with auxiliary contact, voltage release, current limiter, door coupling handles. World-market device, ATEX accreditation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE System-protective circuit-breaker Catalog Number 158243 Model Code

PKE12/AK/XTU-12 EAN 4015081548316 Product Length/Depth 101 mm Product Height 120 mm Product Width 45 mm

Product Weight 0.425 kg Certifications IEC/EN 60947

UL File No.: E36332

CE

CSA

UL 60947-4-1

IEC/EN 60947-4-1

VDE 0660

CSA Class No.: 3211-05

UL

CSA File No.: 165628

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Fitted with: AK lockable rotary handle Functions Overload release

Motor protection

Phase failure sensitive

Motor protection for heavy starting duty Number of poles Three-pole General

Current flow times - min 500 (Class 5) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

1000 (Class 20) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

700 (Class 10) AC-4 cycle operation, Main conducting paths Cut-out periods - min $\leq$ 500 ms, ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE12/AK/XTU-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.