

INDUSTRIAL COMPONENT DATA

PKE32/XTU-36-SOND533 170128 XTPE036BCSNLSOND533 EATON ELECTRIC SOND Motor-protective circuit-breakers, 3-pol..

Brand: EATON - MOELLER | Manufacturer Part Number: PKE32/XTU-36-SOND533



Manufacturer	EATON - MOELLER
MPN / Reference	PKE32/XTU-36-SOND533
Catalog number	Y7-170128
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-E77069B3C8
Generated	2026-08-05

Product Overview

SOND Motor-protective circuit-breakers, 3-pole, 8 - 36A, Standard
PKE32/XTU-36-SOND533

Motor-protective circuit-breaker, Complete device with standard knob, Electronic, 8 - 36 A, With overload release

Motor-protective circuit-breaker complete device (basic device and electronic control unit) according to IEC60947-4-1, electronic wide-range overload protection (4:1), phase-failure and unbalance protection, adjustable tripping class, high short-circuit breaking capacity. Flexible adaptation of the motor-protective circuit's current range through interchangeable electronic release units. Expandable with auxiliary contacts, voltage releases, current limiters, door coupling handles

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE System-protective circuit-breaker Catalog Number 170128 Model Code PKE32/XTU-36-SOND533 EAN 4015081666270 Product Length/Depth 101 mm Product Height 102.5 mm Product Width 45 mm Product Weight 0.436 kg Certifications IEC/EN 60947

VDE 0660 Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (trip blocks) Fitted with: Standard knob Functions Motor protection for heavy starting duty

Phase failure sensitive

Overload release

Motor protection Number of poles Three-pole General

Current flow times - min 900 (Class 15) AC-4 cycle operation, Main conducting paths

1000 (Class 20) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

500 (Class 5) AC-4 cycle operation, Main conducting paths

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

700 (Class 10) AC-4 cycle operation, Main conducting paths Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle operation Degree of protection Terminals: IP00

IP20 Lifespan, electrical 50,000 operations (at 400V, AC-3) Lifespan, mechanical 50,000 Operations (Main conducting paths) O...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE32/XTU-36-SOND533 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.