

INDUSTRIAL COMPONENT DATA

E-PKZ01-PVS 281637 Y7-281637 EATON ELECTRIC Insulated enclosure, flush mounting, +emergency switching off mu..

Brand: EATON - MOELLER | Manufacturer Part Number: E-PKZ01-PVS



Manufacturer	EATON - MOELLER
MPN / Reference	E-PKZ01-PVS
Catalog number	Y7-281637
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-F7E9AAC633
Generated	2026-08-02

Product Overview

Insulated enclosure, flush mounting, +emergency switching off mushroom push-button, key-actuated, for PKZ01 E-PKZ01-PVS

Eaton Moeller® series E-PKZ0 Insulated enclosure, E-PKZ0, H x W x D = 129 x 90 x 176 mm, flush-mounted, + emergency stop mushroom button, key activated

Motor-protective circuit-breaker enclosure for direct integration into the machine

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series E-PKZ0 Accessory Insulated enclosure Catalog Number 281637 Model Code E-PKZ01-PVS EAN 4015082816377 Product Length/Depth 176 mm Product Height 129 mm Product Width 90 mm Product Weight 0.319 kg Certifications CSA Class No.: 3211-05

CSA File No.: 165628

CSA-C22.2 No. 14

UL Category Control No.: NLRV

IEC/EN 60947-4-1

CE

CSA

UL File No.: E36332

UL

UL 508 Features & Functions

Enclosure material Plastic Fitted with: Emergency switching off mushroom push-button

Key-release

PE(N) terminal General

Degree of protection (front side) IP65 Model Built-in Product category Accessories Suitable for Emergency stop Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E-PKZ01-PVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.