

**INDUSTRIAL COMPONENT DATA**

# E-PKZ01-SVB-V 281943 Y7-281943 EATON ELECTRIC

## Insulated enclosure, flush mounting, for PKZ01 +VHI, +padlocki..

Brand: EATON - MOELLER | Manufacturer Part Number: E-PKZ01-SVB-V



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | E-PKZ01-SVB-V                  |
| Catalog number  | Y7-281943                      |
| Category        | Empty enclosure for switchgear |
| Minimum order   | 1 Pcs                          |
| Document ID     | EO-F40B085E32                  |
| Generated       | 2026-08-02                     |

### Product Overview

Insulated enclosure, flush mounting, for PKZ01 +VHI, +padlocking feature yellow

E-PKZ01-SVB-V

Eaton Moeller® series E-PKZ0 Insulated enclosure, E-PKZ0, H x W x D = 129 x 90 x 128 mm, flush-mounted, + VHI, + yellow padlock device

Motor-protective circuit-breaker enclosure for direct integration into the machine

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | EATON - MOELLER > Circuit Breakers PKZ |
|--------------|----------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton Moeller® series E-PKZ0 Accessory Insulated enclosure Catalog Number 281943 Model Code E-PKZ01-SVB-V EAN 4015082819439 Product Length/Depth 128 mm Product Height 129 mm Product Width 90 mm

Product Weight 0.264 kg Certifications CSA-C22.2 No. 14

CSA Class No.: 3211-05

UL Category Control No.: NLRV

IEC/EN 60947-4-1

UL

CSA File No.: 165628

CSA

CE

UL 508

UL File No.: E36332 Features & Functions

Enclosure material Plastic Features Can be locked in 0 position in combination with VHI-PKZ01 Fitted with: PE(N) terminal General

Degree of protection (front side) IP65 Model Built-in Product category Accessories Suitable for Emergency stop Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub> 0 W Heat dissipation capacity P<sub>diss</sub> 0 W Heat dissipation per pole, current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E-PKZ01-SVB-V with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.