

INDUSTRIAL COMPONENT DATA

PKZM0-0,4/NHI-E-11-MTB 229455 Y7-229455 EATON ELECTRIC Motor-Protective Circuit-Breakers 3-pole + 1 N/O + 1 ..

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-0,4/NHI-E-11-MTB



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM0-0,4/NHI-E-11-MTB
Catalog number	Y7-229455
Category	Motor protection circuit-breaker
Minimum order	38 Pcs
Document ID	EO-B018B79365
Generated	2026-08-03

Product Overview

Motor-Protective Circuit-Breakers; 3-pole + 1 N/O + 1 N/C; $I_r = 0.25 - 0.4$ A; screw connection

PKZM0-0,4/NHI-E-11-MTB

Motor-protective circuit-breaker in environmentally friendly reusable shipping container

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

Motor-Protective Circuit-Breakers; 3-pole + 1 N/O + 1 N/C; $I_r = 0.25 - 0.4$ A; screw connection
Motor-protective circuit-breaker in environmentally friendly reusable shipping container
Delivery program

Product rangePKZM0 motor protective circuit-breakers up to 32 A
Basic functionMotor protectionwith integrated NHI-E-11
auxiliary contactNotesAlso suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging.Connection techniqueScrew terminalsMax. motor
ratingAC-3220 V 230 V 240 V [P]0.06 kWAC-3380 V 400 V 415 V [P]0.09 kWAC-3440 V [P]0.12 kWAC-3500 V [P]0.12
kWAC-3660 V 690 V [P]0.18 kWRated uninterrupted current $[I_u] 0.4$ ASetting rangeOverload releases $[I_r] 0.25 - 0.4$
Ashort-circuit release $[I_{rm}]$ max. $[I_{rm}] 6.2$ APhase-failure sensitivityIEC/EN 60947-4-1, VDE 0660 Part 102Explosion
protection (according to ATEX 94/9/EC)? PTB 10, ATEX 3013, Ex II(2) GD

Observe manual MN03402003Z-DE/EN.NotesOverload trigger: tripping class 10 A

Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.Technical data

General Standards IEC/EN 60947, VDE 0660, UL, CSA Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Storage -40 - 80 °C Ambient temperature Open -25 - +55
°C Ambient temperature Enclosed -25 - 40 °C Mounting position Direction of incoming supply as required Degree of
protection Device IP20 Degree of protection Terminations IP00 Protection against direct contact when actuated from front
(EN....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM0-0,4/NHI-E-11-MTB with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.