

INDUSTRIAL COMPONENT DATA

PKZM0-25/NHI11 039430 Y7-39430 EATON ELECTRIC

Motor-protective circuit-breaker, 3p+1N/O+1N/C, Ir 20-25A, scr..

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-25/NHI11



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM0-25/NHI11
Catalog number	Y7-39430
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-7524F21263
Generated	2026-08-06

Product Overview

Motor-protective circuit-breaker, 3p+1N/O+1N/C, Ir=20-25A, screw connection

Switch motor protector; 3 pole + 1 NO + 1 NC; Ir=20-25 To; Connection-screw

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker, 3p+1N/O+1N/C, Ir=20-25A, screw connection

Motor-protective circuit-breaker with pre-assembled standard auxiliary contact as a complete device with assembly-related advantages due to shorter unpacking times

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZM0 Motor-protective circuit-breaker Catalog Number 039430 Model Code PKZM0-25/NHI11 EAN 4015080394303 Product Length/Depth 76 mm Product Height 93 mm Product Width 54 mm Product Weight 0.333 kg Certifications CSA File No.: 165628

UL

UL Category Control No.: NLRV

UL 60947-4-1

IEC/EN 60947

CSA

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

VDE 0660

UL File No.: E36332

CE Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Fitted with: Auxiliary switch Functions Motor protection

Phase failure sensitive Number of poles Three-pole General

Connection Screw terminals Explosion safety category for dust PTB 10, ATEX 3013

Ex II (2) G [Ex eb Gb] [Ex db Gb] [Ex pxb Gb]

Ex II (2) D [Ex tb Db] [Ex pxb Db] Lifespan, electrical 100,000 operations Lifespan, mechanical 100,000 Operations

Mounting position Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height. Operating frequency 40

Operations/h Overvoltage category III Pollution degree 3 Product category Motor protective circuit breaker Protection Finger

and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Shock resistance 25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10

ms Suitable for Branch circuit: Manual type E if used with terminal, or suitable f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM0-25/NH11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.