

INDUSTRIAL COMPONENT DATA

PLANETE 2000 ES ADR CGLine+ LUM17111 EATON ELECTRIC PLANETE200, IP65, CGLINE+

Brand: EATON - MOELLER | Manufacturer Part Number: PLANETE 2000 ES ADR CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	PLANETE 2000 ES ADR CGLine+
Catalog number	LUM17111
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-F2325A5648
Generated	2026-08-04

Product Overview

PLANETE200, IP65, CGLINE+

PLANETE 2000 ES ADR CGLine+

Eaton Planete 2000, Safety lighting, Escape route and open area, CGLine + technology, LED, Non-Maintained operation, IP65, 2000lm, 1 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Central Battery System

Additional Product Information

ETIM for LUM17111 Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Surface mounting/recessed mounting

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)
Battery technology (EF004351)
NiCd
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
2
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
20
Housing material (EF001596)
Plastic
Housing colour (EF000136)
Grey
Material cover (EF004284)
Plastic transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
230 V
Type of control gear (EF000381)
Electronic transformer
Light distributor (EF012170)
Diffuser
Degree of protection (IP) (EF005474)
IP42
Impact strength (EF004293)
IK07
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
4.5 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
2000 lm
Luminous flux in standby mode (EF011954)
3 lm
Colour temperature (EF009346)
5700 K
Power factor (EF025740)
0.55

Nominal operation time (EF012518)

1 h

Width (EF000008)

235 mm

Height/depth (EF001456)

220 mm

Length (EF001438)

400 mm

Built-in width (EF000846)

275 mm

B...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLANETE 2000 ES ADR CGLine+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.