

INDUSTRIAL COMPONENT DATA

XIOC-SER 267191 4519690 EATON ELECTRIC Communication module for XC100/200, 24 V DC, serial, modbus, SUCOM-A,..

Brand: EATON - MOELLER | Manufacturer Part Number: XIOC-SER



Manufacturer	EATON - MOELLER
MPN / Reference	XIOC-SER
Catalog number	4519690
Category	PLC communication module
Minimum order	1 Pcs
Document ID	EO-BE8A89DC11
Generated	2026-08-02

Product Overview

Communication module for XC100/200, 24 V DC, serial, modbus, SUCOM-A, suconet K XIOC-SER

Modular programmable controllers XC-CPU1xx and XC-CPU2xx offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC module) are available. The compact PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. A particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > XC Modular PLC
--------------	----------------------------------

Additional Product Information

General specifications

Product Name Eaton XIOC Communication module Catalog Number 267191 Model Code XIOC-SER EAN 4015082671914

Product Length/Depth 100 mm Product Height 95 mm Product Width 30 mm Product Weight 0.145 kg Certifications CSA

File No.: 012528

UL File No.: E135462

CSA Class No.: 2252-01

UL

CSA

UL Category Control No.: NRAQ

CSA-C22.2 No. 142-M

IEC/EN 61131-2

CSA-C22.2 No. 0-M

CE

UL508

EN 50178 General

Cable type RTS, CTS, DTR, DSR, DCD Current consumption 275 mA (Ie), Interfaces

275 mA, max. internal current consumption, Interface modules Degree of protection IP20 Overvoltage category II Pollution degree 2 Protection class 1 Repetition rate 1 s Residual ripple $\leq 5\%$ Resistance 500 g/? 50 mm ± 25 g (impact resistance)

Type Used with XC100/200 (expandable with up to 15 XI/OC modules) Ambient conditions, mechanical

Shock resistance 15 g, Mechanical, Shock duration 11 ms Vibration resistance 57 - 150 Hz ± 1.0 mm

10 - 57 Hz, ± 0.075 mm Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min

-20 °C Ambient storage temperature - max 70 °C Electro magnetic compatibility

Emitted interference Class A (according to DIN/EN 55011/22) Voltage dips 10 ms Terminal capacities

Terminals Optionally, screw terminals or spring-loaded terminals for digital/analog modules Electrical rating

Power loss 6.6 W Rated operational voltage 24 (12) V DC Supply voltage 20.4 - 28.8 (11.8 - 14.4) V DC, Ad...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XIOC-SER with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.