

INDUSTRIAL COMPONENT DATA

XIOC-TERM30-CNT4 262248 0004519647 EATON ELECTRIC

Plug for XIOC counter modules, 30pole, 4m

Brand: EATON - MOELLER | Manufacturer Part Number: XIOC-TERM30-CNT4



Manufacturer	EATON - MOELLER
MPN / Reference	XIOC-TERM30-CNT4
Catalog number	0004519647
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-1DF16AA43A
Generated	2026-08-04

Product Overview

Plug for XIOC counter modules, 30pole, 4m

XIOC-TERM30-CNT4

Eaton XIOC Plug for XIOC counter modules, 30pole, 4m

Modular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. A particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > XC Modular PLC
--------------	----------------------------------

Additional Product Information

General specifications

Product Name Eaton XIOC Accessory Plug Catalog Number 262248 Model Code XIOC-TERM30-CNT4 EAN

4015082622480 Product Length/Depth 200 mm Product Height 25 mm Product Width 200 mm Product Weight 0.5 kg

Certifications Request filed for UL and CSA Catalog Notes One 18 pole terminal plug is required for each digital and analog module as well as XC modular PLCs. General

Used with XIOC-2CNT-100KHZ

XIOC-1CNT-100KHZ Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,
current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,
non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1
Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance
of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal
heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be
evaluated. 10.2.6 Mechanical impact Does not apply, since the entire switchgear needs t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XIOC-TERM30-CNT4 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.