

INDUSTRIAL COMPONENT DATA

LS-S11S/S 106805 Y7-106805 EATON ELECTRIC Position switch, 1N/O+1N/C, drive for spring-rod actuator

Brand: EATON - MOELLER | Manufacturer Part Number: LS-S11S/S



Manufacturer	EATON - MOELLER
MPN / Reference	LS-S11S/S
Catalog number	Y7-106805
Category	End switch
Minimum order	1 Pcs
Document ID	EO-52914E4539
Generated	2026-08-04

Product Overview

Position switch, 1N/O+1N/C, drive for spring-rod actuator

LS-S11S/S

Eaton Moeller® series LS Position switch, Spring-rod actuator, Complete unit, 1 N/O, 1 NC, Snap-action contact - Yes, Screw terminal, Yellow, Insulated material, -25 - +70 °C, Not to be used as a safety position switch

Position switch, Basic function: Position switches, Part group reference: LS(M)-..., Product range: Spring-rod actuator, Degree of Protection: IP66, IP67, Features: Complete unit, Ambient temperature: -25 - +70 °C, Snap-action contact: Yes, Description: Not to be used as a safety position switch, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Color Enclosure covers: Yellow, Housing: Insulated material, Connection type: Screw terminal, Rod length: 126 mm, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Position switch Catalog Number 106805 Model Code LS-S11S/S EAN 4015081065721 Product Length/Depth 33.5 mm Product Height 180 mm Product Width 31 mm Product Weight 0.078 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 14

UL File No.: E29184

IEC/EN 60947

UL
CSA Class No.: 3211-03
UL 508
UL Category Control No.: NKCR
CE
CSA
IEC/EN 60947-5 Features & Functions
Electric connection type Cable entry metrical Enclosure color Yellow Cover Enclosure material Plastic
Insulated material Features Snap-action contact Switch function type Quick-break switch General
Connection type Screw terminal Degree of protection IP66/IP67
NEMA Other Operating frequency 6000 Operations/h Overvoltage category III Pollution degree 3 Product category
Spring-rod actuator Rated impulse withstand voltage (Uimp) 4000 V AC Repetition accuracy 0.15 mm (Contacts/switching capacity) Type Position switch Ambient conditions, mechanical
Mounting position As required Shock resistance 25 g, Standard-action contact, Mechanical, Half-sinusoidal shock 20 ms
Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Terminal capacities
Terminal capacity (flexible with ferrule) 1 x (0.5 - 1.5) mm² Terminal capacity (solid) 1 x (0.5 - 2.5) mm² Electrical rating
Rated conditional short-circuit current (Iq) 1 k...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-S11S/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.