

## INDUSTRIAL COMPONENT DATA

**AT4/11-S/IA/R316 019484 AT4-11-S-IA-R316 EATON ELECTRIC**  
**Position switch, 1N/O+1N/C, IP65 x, roller lever**

Brand: EATON - MOELLER | Manufacturer Part Number: AT4/11-S/IA/R316



|                 |                  |
|-----------------|------------------|
| Manufacturer    | EATON - MOELLER  |
| MPN / Reference | AT4/11-S/IA/R316 |
| Catalog number  | AT4-11-S-IA-R316 |
| Category        | End switch       |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-C463836675    |
| Generated       | 2026-08-05       |

**Product Overview**

Position switch, 1N/O+1N/C, IP65\_x, roller lever

Position switch; 1 NO + 1 NC; IP65; Roller lever

Position switch, Basic function: Position switches, Safety position switches, Part group reference: AT4, Product range: Rotary lever, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Design: EN 50041 Form A, Snap-action contact: Yes, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Color Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Position Switches

**Additional Product Information**

Position switch, 1N/O+1N/C, IP65\_x, roller leverPosition switch, Basic function: Position switches, Safety position switches, Part group reference: AT4, Product range: Rotary lever, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Design: EN 50041 Form A, Snap-action contact: Yes, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Colour Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947Delivery program

Basic functionPosition switches

Safety position switchesPart group referenceAT4Product rangeRotary leverDegree of ProtectionIP65FeaturesComplete unitAmbient temperature-25 - +70 °CDesignEN 50041 Form ASnap-action contactYesApprovalContactsN/O = Normally

open1 N/ON/C = Normally closed1 NCNotes= safety function, by positive opening to IEC/EN 60947-5-1Contact  
sequenceContact travel? = Contact closed? = Contact openPositive opening (ZW)yesColourEnclosure  
coversGreyEnclosure coversHousingInsulated materialConnection typeScrew terminalNotesThe operating head can be  
rotated at 90° intervals to adapt to the specified approach direction.  
For degree of protection IP65, use V-M20 (206910) cable glands with connecting thread of max. 9 mm length.Technical  
data  
GeneralStandardsIEC/EN 60947Climatic proofingDamp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC  
6006...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AT4/11-S/IA/R316 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.