

INDUSTRIAL COMPONENT DATA

AT4/11-1/I/H 090671 AT4-11-1-I-H EATON ELECTRIC Position switch, 1N/O+1N/C, narrow, IP65 x, actuating rod

Brand: EATON - MOELLER | Manufacturer Part Number: AT4/11-1/I/H



Manufacturer	EATON - MOELLER
MPN / Reference	AT4/11-1/I/H
Catalog number	AT4-11-1-I-H
Category	End switch
Minimum order	1 Pcs
Document ID	EO-40C9FBD267
Generated	2026-08-06

Product Overview

Position switch, 1N/O+1N/C, narrow, IP65_x, actuating rod

Position switch; 1 NO + 1 NC; IP65; Drive rod

Position switch, Basic function: Position switches, Part group reference: AT4, Product range: Actuating rod, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Design: EN 50041 Form D, Description: Not to be used as a safety position switch, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Color Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

Position switch, 1N/O+1N/C, narrow, IP65_x, actuating rodPosition switch, Basic function: Position switches, Part group reference: AT4, Product range: Actuating rod, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Design: EN 50041 Form D, Description: Not to be used as a safety position switch, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Colour Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947Delivery program

Basic functionPosition switchesPart group referenceAT4Product rangeActuating rodDegree of ProtectionIP65FeaturesComplete unitAmbient temperature-25 - +70 °CDesignEN 50041 Form DDescriptionNot to be used as a safety position switchApprovalContactsN/O = Normally open1 N/ON/C = Normally closed1 NCContact sequenceContact travel? = Contact closed? = Contact openColourEnclosure coversGreyEnclosure coversHousingInsulated materialConnection typeScrew terminalNotesThe operating head can be rotated at 90° intervals to adapt to the specified

approach direction.

For degree of protection IP65, use V-M20 (206910) cable glands with connecting thread of max. 9 mm length. Technical data

General Standards IEC/EN 60947 Climatic proofing Damp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30 Ambient temperature -25 - +70 °C Mounting position As required Degree of Protection IP65 Terminal

capacities Solid 1 x (0.75 - 2.5)

2 x (0.75 - 1.5) mm² Terminal c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AT4/11-1/I/H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.