

INDUSTRIAL COMPONENT DATA

AT4/11-S//V 095419 AT4-11-S-I-V EATON ELECTRIC Position switch, 1N/O+1N/C, narrow, IP65 x, adjustable rolle..

Brand: EATON - MOELLER | Manufacturer Part Number: AT4/11-S//V



Manufacturer	EATON - MOELLER
MPN / Reference	AT4/11-S//V
Catalog number	AT4-11-S-I-V
Category	End switch
Minimum order	1 Pcs
Document ID	EO-A0A72FAD55
Generated	2026-08-06

Product Overview

Position switch, 1N/O+1N/C, narrow, IP65_x, adjustable roller lever

Position switch; 1 NO + 1 NC; IP65; Adjustable roller lever

Position switch, Basic function: Position switches, Safety position switches, Part group reference: AT4, Product range: Adjustable roller lever, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Snap-action contact: Yes, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Color Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

Position switch, 1N/O+1N/C, narrow, IP65_x, adjustable roller leverPosition switch, Basic function: Position switches, Safety position switches, Part group reference: AT4, Product range: Adjustable roller lever, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Snap-action contact: Yes, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Colour Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947Delivery program
Basic functionPosition switches
Safety position switchesPart group referenceAT4Product rangeAdjustable roller leverDegree of ProtectionIP65FeaturesComplete unitAmbient temperature-25 - +70 °CSnap-action contactYesApprovalContactsN/O =

Normally open1 N/ON/C = Normally closed1 NCNotes= safety function, by positive opening to IEC/EN 60947-5-1Contact sequenceContact travel? = Contact closed? = Contact openPositive opening (ZW)yesColourEnclosure

coversGreyEnclosure coversHousingInsulated materialConnection typeScrew terminalNotesThe operating head can be rotated at 90° intervals to adapt to the specified approach direction.

For degree of protection IP65, use V-M20 (206910) cable glands with connecting thread of max. 9 mm length.Technical data

GeneralStandardsIEC/EN 60947Climatic proofingDamp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AT4/11-S/I/V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.