

INDUSTRIAL COMPONENT DATA

LS-S11-SW 106807 Y7-106807 EATON ELECTRIC Position switch, 1N/O+1N/C, rounded plunger

Brand: EATON - MOELLER | Manufacturer Part Number: LS-S11-SW



Manufacturer	EATON - MOELLER
MPN / Reference	LS-S11-SW
Catalog number	Y7-106807
Category	End switch
Minimum order	10 Pcs
Document ID	EO-FEF5896426
Generated	2026-08-05

Product Overview

Position switch, 1N/O+1N/C, rounded plunger

LS-S11-SW

Eaton Moeller® series LS Position switch, Rounded plunger, Basic device, expandable, 1 N/O, 1 NC, Screw terminal, Black, Insulated material, -25 - +70 °C

Position switch, Basic function: Position switches, Safety position switches, Part group reference: LS(M)-..., Product range: Rounded plunger, Degree of Protection: IP66, IP67, Features: Basic device, expandable, Ambient temperature: -25 - +70 °C, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Color Enclosure covers: Black, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Position switch Catalog Number 106807 Model Code LS-S11-SW EAN

4015081065745 Product Length/Depth 33.5 mm Product Height 76.5 mm Product Width 31 mm Product Weight 0.052 kg

Certifications CSA Class No.: 3211-03

CSA File No.: 012528

UL 508

UL File No.: E29184

CSA

IEC/EN 60947-5

IEC/EN 60947

CE

UL Category Control No.: NKCR

CSA-C22.2 No. 14

UL Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Electric connection type Cable entry metrical Enclosure color Black (Cover) Enclosure material Plastic

Insulated material Features Expandable

Positive opening

Forced opening Switch function type Quick-break switch General

Connection type Screw terminal Degree of protection IP66/IP67

NEMA Other Operating frequency 6000 Operations/h Overvoltage category III Pollution degree 3 Product category

Rounded plunger Rated impulse withstand voltage (Uimp) 4000 V AC Repetition accuracy 0.15 mm (Contacts/switching capacity) Suitable for Safety functions Type Ambient conditions, mechanical

Mounting position As required Shock resistance 25 g, Standard-action contact, Mechanical, Half-sinusoidal shock 20 ms

Temperature resistance 100 °C, Contact temperature of roller head Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-S11-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.