

INDUSTRIAL COMPONENT DATA

ATR-11-2-IA 210298 EATON ELECTRIC Position switch, 1N/O+1N/C, wide, IP65 x

Brand: EATON - MOELLER | Manufacturer Part Number: ATR-11-2-IA



Manufacturer	EATON - MOELLER
MPN / Reference	ATR-11-2-IA
Catalog number	210298
Category	End switch
Minimum order	1 Pcs
Document ID	EO-F34E405FF9
Generated	2026-08-06

Product Overview

Position switch, 1N/O+1N/C, wide, IP65_x
Position switch 1 NO + 1 NC IP65 Wide box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

Position switch, 1N/O+1N/C, wide, IP65_xIEC EN 60947-5-1, IP65_x, basic device, expandable, device for world markets, modular system, also for use in safety circuits, by positive operation and positive opening contacts, wide version with two cable entries, suitable for use with electronic devices to IEC/EN 61131-2Delivery program

Basic functionPosition switches

Safety position switchesPart group referenceATRProduct rangeRounded plungerDegree of ProtectionIP65FeaturesBasic device, expandableAmbient temperature-25 - +70 °CContactsN/O = Normally open1 N/ON/C = Normally closed1 NCNotes=safety function, by positive opening to IEC/EN 60947-5-1Contact sequenceContact travel? = Contact closed? = Contact openPositive opening (ZW)yesColourEnclosure coversGreyEnclosure coversHousingInsulated materialConnection typeScrew terminalNotesFor degree of protection IP65, use V-M20 (206910) cable glands with connecting thread of max. 9 mm length.Technical data

GeneralStandardsIEC/EN 60947Climatic proofingDamp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30Ambient temperature-25 - +70 °CMounting positionAs requiredDegree of ProtectionIP65Terminal capacitiesSolid1 x (0.75 - 2.5)

2 x (0.75 - 1.5) mm2Terminal capacitiesFlexible with ferrule1 x (0.5 - 1.5)

2 x (0.5 - 1.5) mm² Repetition accuracy 0.02 mm Contacts/switching capacity Rated impulse withstand voltage [U_{imp}] 6000 V
AC Rated insulation voltage [U_i] 500 V Overvoltage category/pollution degree III/3 Rated operational current...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ATR-11-2-IA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.