

INDUSTRIAL COMPONENT DATA

SN3-000-MMEU8 100646 EATON ELECTRIC Moni stabilized power source

Brand: EATON - MOELLER | Manufacturer Part Number: SN3-000-MMEU8



Manufacturer	EATON - MOELLER
MPN / Reference	SN3-000-MMEU8
Catalog number	100646
Category	PLC system power supply
Minimum order	1 Pcs
Document ID	EO-294F6DD5F2
Generated	2026-08-04

Product Overview

Moni stabilized power source

Signal module for the switched-mode power supply units SN3-50-EU8/SN3-100-EU8/SN3-200-EU8, LED display for the states: input o.k./output o.k./remote off relay output 1 changeover contact: Input o.k. relay output 1 changeover contact:output o.k., remote ON-/OFF function for external switching

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery programme Product range Signal module for SN3-...-EU8 power supply unit

Description LED display: Input o.k.

LED display: Output o.k.

LED display: Remote off

Relay output 1 changeover: Input o.k.

Relay output 1 changeover: Output o.k.

Remote ON-/OFF function for external switching

Nominal input voltage 110 - 240 V AC

100 - 350 DC

Input voltage range 70 - 264 V AC

80 - 350 V DC

For use with SN3-50-EU8

SN3-100-EU8

SN3-200-EU8

Technical data General

Standards IEC 61204

73/23/EWG

89/336/EWG

EN 50178, EN 60950, UL 60950, UL 508

Duty factor % 100

Dimensions (W x H x D) mm 56,25 x 54 x 24 (in installed state)

Weight kg 0.065

Terminal capacities mm²Flexible with ferrule mm² 0.2...2.5 (22...14 AWG)Flexible without ferrule mm² 0.2...2.5 (22...14 AWG)Massive mm² 0.2...4 (22...14 AWG)

Degree of protection

Enclosures IP20

Terminals IP20

Protection class 2

Mounting Plugged into power supply unit

Fixing Snap fastener, tool-less

Vibrations (IEC/EN 60068-2-6) 1...57 Hz, amplitude ± 0.075 mm, 57...100 Hz, 5 g

Mechanical shock resistance (IEC 60068-2-27) 5 g all directions

Environmental compatibility

Ambient temperature

Operation °C -25 - +70

Storage °C - 40 - + 85

Climatic proofing 93% at +40°C according to IEC 60068-2-3, no condensation

Climatic class (IEC) 3K3 according to EN 60721

Insulation voltage

Rated insulation voltage U_i V AC 250 nach IEC 60974-1, EN 50178, VDE 0160

Power supply/measuring circuit/relay outputs Safe isolation according to EN 50178, EN 60950

Rated impulse withstand voltage b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SN3-000-MMEU8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.