

INDUSTRIAL COMPONENT DATA

SN3-200-EU8 100645 EATON ELECTRIC Switched-mode power supply unit, 24-28VDC, adjustable, 20A, max. 5 devices..

Brand: EATON - MOELLER | Manufacturer Part Number: SN3-200-EU8



Manufacturer	EATON - MOELLER
MPN / Reference	SN3-200-EU8
Catalog number	100645
Category	PLC system power supply
Minimum order	1 Pcs
Document ID	EO-65EB1CB018
Generated	2026-08-05

Product Overview

Switched-mode power supply unit, 24-28VDC, adjustable, 20A, max. 5 devices switched parallel

Primary pulsed switched-mode power supply unit, input voltage range:85-264VAC or 100-350VDC, output voltage 22-28VDC adjustable, rated output current 20A, power reserves up to 50%, up to 5 devices can be paralleled to increase power and for redundancy, high efficiency up to 90%

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-link, LV, 200 A, AC 600 V, 38 x 146 mm, J, UL, fast acting Fuse, fuse-link, low voltage, 200 A, AC 600 V, 38 x 146 mm, Class J, UL, fast acting, ideal for critical industrial or commercial applications that have specific current limitation requirements. Breaking capacity 200 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 200 A Rated voltage AC 600 V Size 38 x 146 mm Utilization category J Breaking Capacity 200 kA usable for size/applications ideal for critical industrial or commercial applications that have specific current limitation requirements Release characteristic [class] fast-acting Standard/Approval UL , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 200 A Rated voltage 600 V Voltage type AC Rated switching capacity

200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No]

ETIM for 100645 PLC's (EC000599)

Feature Name

Feature Value

Input voltage AC 50 Hz (EF007118)

85 V

Input voltage DC (EF007120)

100 V

Output voltage DC (EF007001)

22 V

Max. output current AC 50 Hz (EF007351)

20 A

Redundancy (EF003156)

No

Suitable for safety functions (EF001597)

No

Width (EF000008)

200 mm

Height (EF0000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SN3-200-EU8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.