INDUSTRIAL COMPONENT DATA

XN-PF-24VDC-D 140070 Y7-140070 EATON ELECTRIC Power supply module XI/ON, 24 V DC

Brand: EATON - MOELLER | Manufacturer Part Number: XN-PF-24VDC-D

Manufacturer	EATON - MOELLER
MPN / Reference	XN-PF-24VDC-D
Catalog number	Y7-140070
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-4443611B6D
Generated	2026-08-03

Product Overview

Power supply module XI/ON, 24 V DC
XN-PF-24VDC-D
Eaton XN Power supply module XI/ON, 24 V DC
Power supply module, Function: XN Slice module, For use with: XN-P3T-SBB, XN-P3S-SBB, XN-P4T-SBBC, XN-P4S-SBBC, Standards: EN 61000-6-2, EN 61000-6-4, EN 61131-2, Degree of Protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications
Product Name Eaton XN Power supply module Catalog Number 140070 Model Code XN-PF-24VDC-D EAN 7640130121027 Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.025 kg
Certifications UL Recognized
UL report applies to both US and Canada
CSA Class No.: 2252-01, 2252-81
UL 508
IEC/EN 6113-2
UL Category Control No.: NRAQ, NRAQ7
IEC/EN 61000-6-2
CE

CSA-C22.2 No. 142
IEC/EN 61000-6-4
IEC/EN 61131-2
CULus
UL File No.: E205091
Certified by UL for use in Canada Features & Functions
Electric connection type Screw-/spring clamp connection Features Fieldbus connection over separate bus coupler possible Fitted with: Potential separation Functions Bus diagnosis possible General
Admissible range 18 - 30 V DC, Supply module Current consumption 28 mA, from module bus, Supply modules Degree of protection IP20 Mounting method Rail mounting possible Product category XN Slice module Residual ripple < 5 % (according to EN 61131-2) Suitable for Base modules with C-connection: 4-wire
Base modules without C-Connection: 2-/3-wire Suitable as Segment module Type XI/ON power supply module Used with
XN-P3T-SBB
XN-P4S-SBBC
XN-P3S-SBB
XN-P4T-SBBC Voltage type DC Ambient conditions, mechanical
Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical, According to IEC/EN 60068-2-27
Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmenta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-PF-24VDC-D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.