

INDUSTRIAL COMPONENT DATA

GW4-050-BA3 200017 EATON ELECTRIC Power supply unit, 1-phase, 230VAC/24VDC, 5A

Brand: EATON - MOELLER | Manufacturer Part Number: GW4-050-BA3



Manufacturer	EATON - MOELLER
MPN / Reference	GW4-050-BA3
Catalog number	200017
Category	PLC system power supply
Minimum order	1 Pcs
Document ID	EO-221DAD86FC
Generated	2026-08-06

Product Overview

Power supply unit, 1-phase, 230VAC/24VDC, 5A

Power supply unit, Product range: GW4 power supply units, Description: unregulated, smoothed, Single-phase, Input voltage range: 230 V AC, Nominal input voltage: 230 V AC, Rated output voltage: 24 V DC, Rated output current: 5 A, For use with: easy..., MFD..., EC4P..., XC-CPU..., XIOC..., PS4..., Degree of Protection: IP20, Fixing: Screw fixing, Heat dissipation: 41 W

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER

Additional Product Information

Power supply unit, 1-phase, 230VAC/24VDC, 5A Power supply unit, Product range: GW4 power supply units, Description: unregulated, smoothed, Single-phase, Input voltage range: 230 V AC, Nominal input voltage: 230 V AC, Rated output voltage: 24 V DC, Rated output current: 5 A, For use with: easy..., MFD..., EC4P..., XC-CPU..., XIOC..., PS4..., Degree of Protection: IP20, Fixing: Screw fixing, Heat dissipation: 41 W [Delivery program

Product range GW4 power supply units Description unregulated

smoothed Phases Single-phase Input voltage range 230 V AC Nominal input voltage 230 V AC Rated output voltage 24 V DC Rated output current 5 A For use with easy...

MFD...

EC4P...

XC-CPU...

XIOC...

PS4... , Technical data

General Protection class 1 Potential isolation Yes, VDE 0551, IEC/EN 60742, SELV Supply frequency Rated value 50/60 Hz
Electromagnetic compatibility (EMC) Emitted interference Class B (EN 55011, 22) Electromagnetic compatibility (EMC) ESD
[Air/contact discharge] 6 kV contact (Level 3), 8 kV air (Level 3), IEC/EN 61000-4-2 kV Electromagnetic compatibility
(EMC) RFI 10 V/m, modulated, IEC/EN 61000 4-2 Electromagnetic compatibility (EMC) Burst 2 kV (Level 3) IEC/EN
61000-4-4 Electromagnetic compatibility (EMC) Surge 2 kV (Inst. Class 3), IEC/EN 61000-4-5 Electromagnetic compatibility
(EMC) Surge voltage 4.9 kV, IEC EN 60947 Environmental compatibility Ambient temperature -25 - 55 Environmental
compatibility Ambient temperature, storage - -25 - 85 °C Environmental compatibility Overvoltage category/pollution....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GW4-050-BA3 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.