

INDUSTRIAL COMPONENT DATA

AING4 269516 Y7-269516 EATON ELECTRIC Power supply unit, 1p, 100VA, prim 230VAC, sec. 24VAC, 24 V DC, 10 V DC

Brand: EATON - MOELLER | Manufacturer Part Number: AING4



Manufacturer	EATON - MOELLER
MPN / Reference	AING4
Catalog number	Y7-269516
Category	PLC system power supply
Minimum order	1 Pcs
Document ID	EO-44FF3861F3
Generated	2026-08-05

Product Overview

Power supply unit, 1p, 100VA, prim 230VAC, sec. 24VAC, 24 V DC, 10 V DC

AING4

Eaton Moeller® series AING Power supply unit, 1p, 100VA, prim 230VAC, sec. 24VAC, 24 V DC, 10 V DC

Universal power supply unit single-phase, safety transformer to IEC/EN 61558-2-2, 2-6, VDE 0570 Part 2-2, 2-6. rated power 100VA, one fuse per output voltage, a changeover contact for monitoring and annunciation, rated input voltage 230V +- 5%, rated output voltage / current: 24V AC / 4.2A, 10V DC / 1A, 24V DC / 3A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Transformers

Additional Product Information

General specifications

Product Name Eaton Moeller® series AING Power supply unit Catalog Number 269516 Model Code AING4 EAN

4015082695163 Product Length/Depth 90 mm Product Height 155 mm Product Width 110 mm Product Weight 3.1 kg

Certifications VDE 0570 Part 2-2/2-6 (safety transformer)

IEC/EN 60204-1

VDE 0113

Safety transformer to IEC/EN 61558-2-2/2-6 Catalog Notes Non-standard voltages on request Features & Functions

Features Fully Vacuum-impregnated

Separate windings

Reinforced insulation General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Connection type Terminations
Degree of Protection IP20 Degree of Protection IP20 Duty factor 100 % Insulation class B Primary tapping $\pm 5\%$ Product
category Universal power supply unit AING Suitable for Safety functions Type Single-phase power supply Electrical rating
Input current at AC - max 0.44 A Input voltage at AC 50 Hz - min 230 V Input voltage at AC 50 Hz - max 230 V Input voltage
at DC - min 0 V Input voltage at DC - max 0 V Output current at AC, 50 Hz - max 4.2 A Output voltage at AC 50 Hz - max
24 V Output voltage at DC - min 24 V Output voltage at DC - max 24 V Rated frequency - min 50 Hz Rated frequency - max
60 Hz Rated power 0.1 VA Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,
current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AING4 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.