

INDUSTRIAL COMPONENT DATA

STB-M25F 224558 0001706011 EATON ELECTRIC Pressure compensating ventilation gland, M25, IP56 x

Brand: EATON - MOELLER | Manufacturer Part Number: STB-M25F



Manufacturer	EATON - MOELLER
MPN / Reference	STB-M25F
Catalog number	0001706011
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-9197FEF6C7
Generated	2026-08-05

Product Overview

Pressure compensating ventilation gland, M25, IP56_x

Mounting Accessory

Threaded ventilation connection M25, degree of protection IP56, RAL 7035, permeable to air, un-permeable to dust, fitting below or on side of enclosure, for prevention of condensation, cable entry=M25, drilling dimensions=25.5mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

EL-Nummer (Norway)1706011Pressure compensating ventilation gland, M25, IP56Threaded ventilation connection M25, degree of protection IP56, RAL 7035, permeable to air, un-permeable to dust, fitting below or on side of enclosure, for prevention of condensation, cable entry=M25, drilling dimensions=25.5mmDelivery program

AccessoriesVentilation cable glandDescriptionPermeable to air, un-permeable to dust

Fitting below or on side of enclosureFunctionFor the prevention of condensationMaterialglass-fibre reinforced polyamide Halogen free

with flame protection, self-extinguishingCable entryM25Hole diameter25,5 mmColourRAL 7035Degree of ProtectionIP56, mounting below or on side of enclosure onlyFor use withCS-...

Ci...

EW...

XVTL

xEnergyTechnical data

GeneralDegree of ProtectionIP56, mounting below or on side of enclosure onlyMaterial characteristicsMaterialglass-fibre reinforced polyamide
Halogen free
with flame protection, self-extinguishingColourRAL 7035Temperature resistant-40 °C - 100 °C, short-time up to approx. 150 °CChemical resistantResistant against : Acetone, petrol, paraffin, diesel, grease, oil, solvent for paints and varnishesDanger of stress fracturelowFlame retardantGlow wire test 750 °C according to EN 60695-2-11Technical data ETIM 7.0
Cable and wire entry systems (EG000009) / Cable gland (EC000441)Electric engineering, automation, process control engineering / Electrical installation, device / Connection devices / Screwed cable gland (electr.) () [AFR797...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / STB-M25F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.