

INDUSTRIAL COMPONENT DATA

MCS22-U 012592 EATON ELECTRIC Pressure switch, 1W, 25bar

Brand: EATON - MOELLER | Manufacturer Part Number: MCS22-U



Manufacturer	EATON - MOELLER
MPN / Reference	MCS22-U
Catalog number	012592
Category	Pressure switch
Minimum order	1 Pcs
Document ID	EO-76B8503E13
Generated	2026-08-01

Product Overview

Pressure switch, 1W, 25bar

Switched pressure switch 1 25 bar

Eaton Moeller® series MCS Pressure switch, 1W, 25bar MCS22-U

IEC EN 60947-5-1, IP65_x, pressure monitoring of liquid and gaseous media, e. g. compressed air, for actuation of the auxiliary circuits, make and break pressure: separately adjustable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series MCS Pressure switch Catalog Number 012592 Model Code MCS22-U EAN 4015080125921 Product Length/Depth 96 mm Product Height 111 mm Product Width 60 mm Product Weight 0.28 kg Certifications IEC/EN 60947-5-1 Catalog Notes Note on use: This product complies with Low-Voltage Directive 2014/35/EC and EMC Directive 2014/30/EC and meets the requirements in EN 60947-5-1. This product does not meet the rail industry's standard requirements. Accordingly, the user must review it separately for the specific application at hand. Features & Functions

Electric connection type Screw connection Features Variable switching differential General

Actuator diameter 0 mm Bursting pressure 90 bar Connection Inner thread gas cylindrical (BSPP) Connection type Tunnel terminal Degree of protection IP65

NEMA Other Operating pressure - max 25000 hPa Overvoltage category III Pollution degree 3 Product category Pressure

switches Rated impulse withstand voltage (Uimp) 4000 V AC Suitable as 2-point controller
Guard Test pressure 32 bar Ambient conditions, mechanical
Mounting position As required Shock resistance 10 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock
20 ms Vibration resistance 36 Hz, Amplitude 1 mm, (IEC/EN 60068-2-6) Climatic environmental conditions
Ambient operating temperature - min 25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MCS22-U with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.