

INDUSTRIAL COMPONENT DATA

MCS11-G 058692 Y7-58692 EATON ELECTRIC Pressure switch, 1W gold-plated, 15bar

Brand: EATON - MOELLER | Manufacturer Part Number: MCS11-G



Manufacturer	EATON - MOELLER
MPN / Reference	MCS11-G
Catalog number	Y7-58692
Category	Pressure switch
Minimum order	1 Pcs
Document ID	EO-69D855D92C
Generated	2026-08-05

Product Overview

Pressure switch, 1W gold-plated, 15bar

Switching pressure switch 1 gold-plated 15 bar

Eaton Moeller® series MCS Pressure switch, 1W gold-plated, 15bar

IEC EN 60947-5-1, IP65_x, pressure monitoring of liquid and gaseous media, e. g. compressed air, for actuation of the auxiliary circuits, make and break pressure: separately adjustable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series MCS Pressure switch Catalog Number 058692 Model Code MCS11-G EAN

4015080586920 Product Length/Depth 96 mm Product Height 111 mm Product Width 60 mm Product Weight 0.383 kg

Certifications CSA-CC22.2 No. 14

IEC/EN 60947-5-1

CSA File No.: 012528

CSA Class No.: 3211-06

CSA Catalog Notes Features & Functions

Electric connection type Screw connection Features Variable switching differential General

Actuator diameter 0 mm Bursting pressure 90 bar Connection Inner thread gas cylindrical (BSPP) Connection type Tunnel terminal Degree of protection IP65

NEMA Other Lifespan, electrical 1,000,000 Operations Operating frequency 1500 Operations/h Operating pressure - max 15000 hPa Overvoltage category III Pollution degree 3 Product category Pressure switches Rated impulse withstand voltage (Uimp) 4000 V AC Suitable as 2-point controller

Guard Test pressure 32 bar Ambient conditions, mechanical

Mounting position Vertical and 90° in all directions Shock resistance 10 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms Vibration resistance 36 Hz, Amplitude 1 mm, (IEC/EN 60068-2-6) Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Environmental conditions Compliant to 2014/35/EC, 2014/30/EC and EN 60947-5-1. Accordingly, the user must review it separatel...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MCS11-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.