

INDUSTRIAL COMPONENT DATA

CU-BAR-720/T 107167 Y7-107167 EATON ELECTRIC Profile busbar, T, cu, 720mm², tin-plated 2.40 m

Brand: EATON - MOELLER | Manufacturer Part Number: CU-BAR-720/T



Manufacturer	EATON - MOELLER
MPN / Reference	CU-BAR-720/T
Catalog number	Y7-107167
Category	Busbar
Minimum order	1 Pcs
Document ID	EO-8A26C3C99C
Generated	2026-08-05

Product Overview

Profile busbar, T, cu, 720mm², tin-plated 2.40 m

CU-BAR-720/T

Rigid busbar double T, SASY60i and SASY185i, surface tin-coated, busbar cross-section=720mm², supplied in lengths=2400mm, Ie=1600A, for busbar support BBS -3/Engineering Guidelines, BBS-1/PR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

Profile busbar, T, cu, 720mm², tin-plated 2.40 m Rigid busbar double T, SASY60i and SASY185i, surface tin-coated, busbar cross-section=720mm², supplied in lengths=2400mm, Ie=1600A, for busbar support BBS -3/Engineering Guidelines, BBS-1/PR

General specifications Product name Eaton xEffect SASY 60i copper busbar profiled Part

no. CU-BAR-720/TEAN4015081069309 Product Length/Depth 2400 millimetre Product height 40 millimetre Product width 30 millimetre Product weight 15.4 kilogram Compliances UL CSA09 (refer to approbation report)

IEC 60439-1

CE marking

CSA-C22.2 No. 14

UL508A

RoHS conform Certifications EN 13061

UL (File No. E300273)

CSA (Class No. 3211-37)

CSA (File No. 236217)

UL (Category Control Number NMTR, NMTR7)

UL 508

North America (UL listed, CSA certified)Product TradenamexEffect SASY 60iProduct TypeCopper busbarProduct Sub

TypeProfiledDelivery programType185 mm system

60 mm system

System for profile busbarModelProfileNominal current1600 ATechnical Data - ElectricalVoltage rating (UL CSA 13)Max. 600

V ACRated uninterrupted current (Iu) of conductor1200 A (720 mm², Tu=35 °C and Ts=65 °C)

950 A (500 mm², Tu=35 °C and Ts=65 °C)Rated operation current (Ie)1600 ATechnical Data - MechanicalSurface

protectionTinnedCross section720 mm²MaterialCopper, tinnedDegree of protectionFeeder circuitsDistance between busbar centers60 mm

185 mmAdditional informationFunctionsCurrent limiting circuit breaker, refer to approbation report

System for profile busbars

E-CU double T profile busbar

Profiled bus...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU-BAR-720/T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.