

## INDUSTRIAL COMPONENT DATA

# DILK20-11(230V50HZ,240V60HZ) 294010 Y7-294010 EATON ELECTRIC Contactor for 3ph three-phase capacitors, 20kVAR

Brand: EATON - MOELLER | Manufacturer Part Number: DILK20-11(230V50HZ,240V60HZ)



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | EATON - MOELLER              |
| MPN / Reference | DILK20-11(230V50HZ,240V60HZ) |
| Catalog number  | Y7-294010                    |
| Category        | Capacitor contactor          |
| Minimum order   | 1 Pcs                        |
| Document ID     | EO-3B6E99904B                |
| Generated       | 2026-08-05                   |

## Product Overview

Contactor for 3ph three-phase capacitors, 20kVAR

DILK20-11(230V50HZ,240V60HZ)

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 20 kVAr, 230 V 50 Hz, 240 V 60 Hz

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                         |
|--------------|-----------------------------------------|
| Catalog path | EATON - MOELLER > Contactors up to 170A |
|--------------|-----------------------------------------|

## Additional Product Information

### General specifications

Product Name Eaton Moeller® series DILK capacity contactor Catalog Number 294010 Model Code

DILK20-11(230V50HZ,240V60HZ) EAN 4015082940102 Product Length/Depth 138 mm Product Height 135 mm Product Width 45 mm Product Weight 0.51 kg Certifications CSA Certified

UL Listed

CSA File No.: 012528

CSA

CSA Class No.: 3211-04

CE

IEC/EN 60947-4-1

IEC/EN 60947

UL

UL Category Control No.: NLDX

UL File No.: E29096

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14 Features & Functions

Fitted with: Series resistors General

Application Contactors for power factor correction Lifespan, electrical 150,000 Operations Operating frequency 120 Operations/h Product category DILK Contactors for capacitors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Electro Magnetic Compatibility

Emitted interference According to EN 60947-1 Interference immunity According to EN 60947-1 Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.75 - 16) mm<sup>2</sup>, Main cables Terminal capacity (solid) 1 x (0.75 - 16) mm<sup>2</sup>, Main cables Terminal capacity (solid/stranded AWG) 18 - 6, Main cables Terminal capacity (stranded) 1 x 16 mm<sup>2</sup>, Main cables

Electrical Rating

Rated operational current (I<sub>e</sub>) 29 A a...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILK20-11(230V50HZ,240V60HZ) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.