

INDUSTRIAL COMPONENT DATA

DILK25-11(48V50HZ) 294022 Y7-294022 EATON ELECTRIC

Contactor for 3ph three-phase capacitors, 25kVAR

Brand: EATON - MOELLER | Manufacturer Part Number: DILK25-11(48V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILK25-11(48V50HZ)
Catalog number	Y7-294022
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-56DEA7AFD6
Generated	2026-08-05

Product Overview

Contactor for 3ph three-phase capacitors, 25kVAR

DILK25-11(48V50HZ)

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 25 kVAr, 48 V 50 Hz

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILK capacity contactor Catalog Number 294022 Model Code DILK25-11(48V50HZ)

EAN 4015082940225 Product Length/Depth 138 mm Product Height 135 mm Product Width 45 mm Product Weight 0.51 kg

Compliances CE Marked Certifications IEC 60947-4-1

CSA Std. C22.2 No. 14-05

UL 508

EN 60947-4-1

VDE

CE

CSA

UL File No.: E29096

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CSA Class No.: 3211-04

IEC/EN 60947-4-1

UL

UL 60947-4-1

CSA File No.: 012528

UL Category Control No.: NLDX Features & Functions

Fitted with: Series resistors General

Application Contactors for power factor correction Lifespan, electrical 150,000 Operations Operating frequency 120

Operations/h Product category DILK Contactors for capacitors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Electro Magnetic Compatibility

Emitted interference According to EN 60947-1 Interference immunity According to EN 60947-1 Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.75 - 16) mm², Main cables Terminal capacity (solid) 1 x (0.75 - 16) mm², Main cables Terminal capacity (solid/stranded AWG) 18 - 6, Main cables Terminal capacity (stranded) 1 x 16 mm², Main cables Elec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILK25-11(48V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.