

INDUSTRIAL COMPONENT DATA

DILK33-10(190V50HZ,220V60HZ) 294052 Y7-294052 EATON ELECTRIC Contactor for 3ph three-phase capacitors, 33.3k..

Brand: EATON - MOELLER | Manufacturer Part Number: DILK33-10(190V50HZ,220V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILK33-10(190V50HZ,220V60HZ)
Catalog number	Y7-294052
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-74D79FF93B
Generated	2026-08-05

Product Overview

Contactor for 3ph three-phase capacitors, 33.3kVAR

DILK33-10(190V50HZ,220V60HZ)

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 33.3 kVAr, 190 V 50 Hz, 220 V 60 Hz

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILK capacity contactor Catalog Number 294052 Model Code

DILK33-10(190V50HZ,220V60HZ) EAN 4015082940522 Product Length/Depth 147 mm Product Height 190 mm Product Width 55 mm Product Weight 1.02 kg Certifications CSA C22.2.

UL Listed

IEC 60947-4-1

EN 60947-4-1

CSA Class No.: 3211-04

IEC/EN 60947

UL File No.: E29096

UL

CE

CSA

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-4-1

UL Category Control No.: NLDX

UL 60947-4-1 Features & Functions

Fitted with: Series resistors General

Application Contactors for power factor correction Lifespan, electrical 150,000 Operations Operating frequency 120 Operations/h Product category DILK Contactors for capacitors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Voltage type AC Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Electro Magnetic Compatibility Emitted interference According to EN 60947-1 Interference immunity According to EN 60947-1 Terminal capacities Terminal capacity (copper band) 1 x (6 x 9 x 0.8) mm (Number of segments x width x thickness), Main cables Terminal capacity (flexible with ferrule) 1 x (2.5 - 35) mm², Main cables Terminal capacity (solid) 1 x (2.5 - 16) mm², Main cables Terminal capacity (solid/stranded AWG)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILK33-10(190V50HZ,220V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.