

INDUSTRIAL COMPONENT DATA

MFD-XS-80 265259 0004519708 EATON ELECTRIC Protective cover for MFD-80(-B), can be sealed, transparent

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-XS-80



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-XS-80
Catalog number	0004519708
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-BDB7AE5B6B
Generated	2026-08-05

Product Overview

Protective cover for MFD-80(-B), can be sealed, transparent

Sealable protective cover; For MFD-80...

Protection cover, transparent, for protection against accidental actuation, can be sealed, can be used for MFD-80... sans front frame

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

Protective cover for MFD-80(-B), can be sealed, transparent Protection cover, transparent, for protection against accidental actuation, can be sealed, can be used for MFD-80... sans front frame Delivery program

Product range Multi-function-display MFD-Titan Accessories Protective cover Description Transparent

Protection against accidental actuation

sealable

Application without front frames For use with MFD-80... Information relevant for export to North America Product Standards IEC/EN see Technical Data; UL 508; CSA C22.2 No. 142-M1987; CSA C22.2 No. 213-M1987; CE marking

UL File No. E135462

UL Category Control No. NRAQ

CSA File No. 012528

CSA Class No. 2252-01 + 2258-02

North America Certification UL listed, CSA certified

Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +55 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.2 Verification...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-XS-80 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.