

INDUSTRIAL COMPONENT DATA

E57EBL8T110ED 136254 Y7-136254 EATON ELECTRIC

Proximity switch, inductive, 1 N/C, Sn 2mm, 3L, 10-30VDC, NPN,..

Brand: EATON - MOELLER | Manufacturer Part Number: E57EBL8T110ED



Manufacturer	EATON - MOELLER
MPN / Reference	E57EBL8T110ED
Catalog number	Y7-136254
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-8FD29C20F9
Generated	2026-08-05

Product Overview

Proximity switch, inductive, 1 N/C, Sn=2mm, 3L, 10-30VDC, NPN, M8mm, M12

E57EBL8T110ED

Proximity switch, E57 Miniatur Series, 1 NC, 3-wire, 10 - 30 V DC, M8 x 1 mm, Sn= 2 mm, Non-flush, NPN, Stainless steel, Plug-in connection M12 x 1

Proximity switch, Inductive Sensors, Product range: E57 Miniature Series, Connection: 3-wire, Design (outer dimensions): M8 x 1 mm, Rated operational voltage: $U_e = 10 - 30 \text{ V DC}$, Rated switching distance: $S_n = 2 \text{ mm}$, Type of mounting: Non-flush, Switching type: NPN, Plug-in connection M12 x 1, Contacts N/C = Normally closed: 1 NC, Material: Stainless steel, Degree of Protection: IP67, Standards: IEC/EN 60947-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series E57 Proximity switch Catalog Number 136254 Model Code E57EBL8T110ED EAN 4015081330478 Product Length/Depth 45.72 mm Product Height 86.36 mm Product Width 45.72 mm Product Weight 0.03 kg Certifications CE

IEC/EN 60947-5 Product specifications

Type Inductive sensor Electric connection type Connector M12 Enclosure material finishing Other Actuation type Metallic

Target Enclosure material Metal Enclosure type Cylinder, screw-thread Category (EN 954-1) B Explosion safety category for dust None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Diameter sensor 8 mm Number of contact energized outputs with signalling function 0 Number of contacts (normally closed contacts) 1 Number of outputs (protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 10 A Output current at protected output - max 0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Functions Short-circuit protection Voltage type DC Mounting method Non-flush mounting Material Stainless steel Connection type 3-wire Plug-in connection M12 x 1 Installation type Not flat Degree of protection IP67 NEMA 6P Interface type None LED indicator Status indication of Switching state: Red LED...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57EBL8T110ED with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.