

INDUSTRIAL COMPONENT DATA

E57-12GE08-D 135871 Y7-135871 EATON ELECTRIC Proximity switch, inductive, 1N/O, Sn 8mm, 2L, 10-30VDC, M12, m..

Brand: EATON - MOELLER | Manufacturer Part Number: E57-12GE08-D



Manufacturer	EATON - MOELLER
MPN / Reference	E57-12GE08-D
Catalog number	Y7-135871
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-FA14A54B82
Generated	2026-08-06

Product Overview

Proximity switch, inductive, 1N/O, Sn=8mm, 2L, 10-30VDC, M12, metal, line 2m

E57-12GE08-D

Proximity switch, E57 Global Series, 1 N/O, 2-wire, 10 - 30 V DC, M12 x 1 mm, Sn= 8 mm, Non-flush, NPN/PNP, Metal, 2 m connection cable

Proximity switch, Inductive Sensors, Product range: E57 Global Series, Connection: 2-wire, Design (outer dimensions): M12 x 1 mm, Rated operational voltage: Ue= 10 - 30 V DC, Rated switching distance: Sn= 8 mm, Type of mounting: Non-flush, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Metal, Degree of Protection: IP67, IP69K, Standards: IEC/EN 60947-5-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series E57 Proximity switch Catalog Number 135871 Model Code E57-12GE08-D EAN 4015081326648 Product Length/Depth 165.1 mm Product Height 12.7 mm Product Width 139.7 mm Product Weight 0.16 kg Certifications CSA-C22.2 No. 14

UL 508

IEC/EN 60947-5-2

CE

CSA File No.: 224447

UL File No.: CSA report applies to both US and Canada

CSA Class No.: 4652-04 / 4652-84

CSA Product specifications

Type Inductive sensor Electric connection type Cable Enclosure material finishing Other Actuation type Metallic Target
Enclosure material Metal Enclosure type Cylinder, screw-thread Category (EN 954-1) B Explosion safety category for dust
None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None
Ambient operating temperature - max 60 °C Ambient operating temperature - min 0 °C Diameter sensor 12 mm Number of
contact energized outputs with signalling function 0 Number of contacts (normally open contacts) 1 Number of outputs
(protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with
signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 10 A Output current at protected output - max
0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Voltage type DC Mounting method Non-flush mounting
Material Metal Connection type 2 m connection cable
2-wire Installation type Not flat Degree of protection IP67
IP69
NEMA Oth...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57-12GE08-D with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.