

INDUSTRIAL COMPONENT DATA

PSG960R24RM 172889 EATON ELECTRIC Redundancy module for PSG power supply units, 40 A

Brand: EATON - MOELLER | Manufacturer Part Number: PSG960R24RM



Manufacturer	EATON - MOELLER
MPN / Reference	PSG960R24RM
Catalog number	172889
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-43BC0A8037
Generated	2026-08-05

Product Overview

Redundancy module for PSG power supply units, 40 A

Redundancy module for power supply units, for decoupling power supplies of the same type that are connected in parallel on the output side for redundancy purposes, input voltage range 22-60 VDC, output current 40 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Transformers
--------------	--------------------------------

Additional Product Information

Redundancy module for PSG power supply units, 40 A Alternate Catalog No. PSG960R24RM EL-Nummer (Norway) 4560887 Redundancy module for power supply units, for decoupling power supplies of the same type that are connected in parallel on the output side for redundancy purposes, input voltage range 22-60 VDC, output current 40 A [Delivery program Product range Power supplies PSG Subrange Redundancy module Description For decoupling power supplies of the same type that are connected in parallel on the output side for redundancy purposes Input voltage range 22 - 60 V DC Nominal input voltage 24 - 48 V DC Rated output voltage Vin- 0.65 V Rated output current 40 A , Technical data Input characteristics Nominal input voltage 24 - 48 V DC Input voltage range 24 - 48 V DC V Eingangsspannungsalarm_Relaiskontakt Relay contact closed "OK" if Vin1 & Vin2 > 18 V +/- 5% and < 30 V Nominal current [In] (1+1) Redundanz : Nom. 2 x 25 (N+1) Redundanz : Nom. 2 x 20 Einfache Nutzung : Nom. 1 x 40 A Back-up fuse 3 x 6, 10, 16 A (recommended) Output characteristics Rated output voltage Vin- 0.65 V Nominal current max. 40 A Derating from Tamb> +50 °C > 50 °C (2.5% / °C) Heat dissipation 26 W Efficiency 97 % norm. % Short-circuit current < 25 A, no damage General characteristics Housing Aluminium MTBF (mean time

between failures) > 800,000 h Height 121 mm Width 50 mm Depth 122 mm Weight 0.52 kg Terminations Screw connection
Terminal capacityflexible with ferrules/solid 3.3 - 5.3 mm² (AWG 12 - 10) mm2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PSG960R24RM with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.