

INDUSTRIAL COMPONENT DATA

M22-I3-M1 216532 Y7-216532 EATON ELECTRIC Pushbutton actuator, 3N/O+3N/C, surface mounting

Brand: EATON - MOELLER | Manufacturer Part Number: M22-I3-M1



Manufacturer	EATON - MOELLER
MPN / Reference	M22-I3-M1
Catalog number	Y7-216532
Category	Control circuit devices combination in enclosure
Minimum order	1 Pcs
Document ID	EO-B4966A0DC8
Generated	2026-08-02

Product Overview

Pushbutton actuator, 3N/O+3N/C, surface mounting

M22-I3-M1

Eaton Moeller® series M22 Housing, Pushbutton actuators, Enclosure, momentary, 3 NC, 3 N/O, Screw connection, Number of locations 3, Grey, inscribed, Bezel: titanium

Housing, Product range: RMQ-Titan, Complete unit, Design: Enclosure, momentary, Connection type: Screw connection, Number of locations: 3 Qty., Color Enclosure covers: Grey, Color RAL Value: RAL 7035, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 3 NC, Contacts N/O = Normally open: 3 N/O, Contacts Notes = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.8, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Front dimensions: 153 x 80, Standards: IEC/EN 60947, VDE 0660 , Mounting position: As required

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Housing Catalog Number 216532 Model Code M22-I3-M1 EAN 4015082165321
Product Length/Depth 80 mm Product Height 70 mm Product Width 153 mm Product Weight 0.333 kg Certifications IEC/EN 60947

CE

VDE 0660

CSA-C22.2 No. 94-91

CSA Class No.: 3211-03

UL

UL 508

CSA File No.: 012528

UL File No.: E29184

CSA-C22.2 No. 14-05

UL Category Control No.: NKCR

CSA

IEC/EN 60947-5 Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1

ETIM for 216532 Low-voltage industrial controls and switchgear (EC000225)

Feature Name

Feature Value

Number of command positions (EF001372)

3

Number of push buttons (EF005558)

3

Number of indicator lights (EF001965)

0

Number of key switches (EF005590)

0

Number of selector switches (EF005567)

0

Number of mushroom-shaped push-buttons (EF006670)

0

Suitable for emergency stop (EF001433)

No

Rated control supply voltage AC 50 Hz (EF003978)

115 V

Rated control supply voltage AC 60 Hz (EF003979)

115 V

Rated control supply voltage DC (EF003980)

24 V

Colour housing cover (EF001373)

Grey

Housing colour (EF000136)

Grey

Housing material (EF001596)

Plastic

Number of contacts as normally open contact (EF008256)

2

Number of contacts as normally closed contact (EF008255)

2

Number of contacts as change-over contact (EF008257)

0

Degree of protection (IP) (EF005474)

IP67/IP69K

Degree of protection (NEMA) (EF011959)

4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-I3-M1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.