

INDUSTRIAL COMPONENT DATA

M22-DDL-*.~.* 226770 Y7-226770 EATON ELECTRIC Double actuator pushbutton, +indicator light, white , white, o..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DDL-*.~.*



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DDL-*.~.*
Catalog number	Y7-226770
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-8653EA1878
Generated	2026-08-02

Product Overview

Double actuator pushbutton, +indicator light, white , white, off switch raised black, facility for inscription

M22-DDL-*.~.*

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, selectable, individual facility for inscription, Bezel: titanium

Double actuator pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators and indicator lights non-flush, momentary, Description: White lens, button plate: selectable, Button plate individual facility for inscription, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7 x 54,7, Ordering information: Notes on customized inscription -> Data sheet, additional product information (links), Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Double actuator pushbutton Catalog Number 226770 Model Code

M22-DDL-*.~.* Product Length/Depth 30 mm Product Height 55 mm Product Width 30 mm Product Weight 0.015 kg

Certifications VDE 0660

CSA

CSA-C22.2 No. 14-05

UL

UL Category Control No.: NKCR

CSA Class No.: 3211-03

CSA File No.: 012528

CSA-C22.2 No. 94-91

IEC/EN 60947

IEC/EN 60947-5

CE

UL 508

UL File No.: E29184

DNV

GL

LR Catalog Notes Notes on customized inscription -> Data sheet, additional product information (links) Features & Functions

Bezel color Titanium Bezel material Plastic Design Non-Flush

Classical Features Labelled Fitted with: Front ring Inscription Individual inscription possible Lens color White General

Degree of protection NEMA 4X

NEMA 12

NEMA 3R

NEMA 13

IP66 Degree of protection (front side) IP66

NEMA 4X Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h

Product category RMQ-Titan Size Front dimensions: 29,7 x 54,7 mm Suitable for Illumination Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp he...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DDL-*-*-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.