

INDUSTRIAL COMPONENT DATA

M22-DDLM-GR-X1/X0 284830 Y7-284830 EATON ELECTRIC

Double actuator pushbutton, +indicator light, flush, green..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DDLM-GR-X1/X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DDLM-GR-X1/X0
Catalog number	Y7-284830
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-3DCD10456A
Generated	2026-08-04

Product Overview

Double actuator pushbutton, +indicator light, flush, green I, white, off switch raised red O

M22-DDLM-GR-X1/X0

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Pushbutton actuator I and indicator light flush, pushbutton actuator O non-flush, momentary, White lens, green, red, inscribed, Bezel: titanium

Double actuator pushbutton, Product range: RMQ-Titan, Single unit, Design: Pushbutton actuator I and indicator light flush, pushbutton actuator O non-flush, momentary, Description: White lens, button plate: green, red, Button plate inscribed, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7 x 54,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Double actuator pushbutton Catalog Number 284830 Model Code

M22-DDLM-GR-X1/X0 EAN 4015082848309 Product Length/Depth 30 mm Product Height 55 mm Product Width 30 mm

Product Weight 0.015 kg Certifications IEC/EN 60947-5

CSA-C22.2 No. 14-05

IEC/EN 60947

CSA-C22.2 No. 94-91

UL 508

CE

VDE 0660

DNV

GL

LR Catalog Notes Boton doble grabado I/O Features & Functions

Bezel color Titanium Bezel material Plastic Design Pushbutton actuator I and indicator light flush, pushbutton actuator 0 non-flush

Classical Features Labelled Fitted with: Front ring Inscription Inscribed Lens color White General

Degree of protection IP66

NEMA 12

NEMA 4X

NEMA 3R

NEMA 13 Degree of protection (front side) NEMA 4X

IP66 Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h Product category RMQ-Titan Size Front dimensions: 29,7 x 54,7 mm Suitable for Illumination Type Double actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DDLM-GR-X1/X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.