

INDUSTRIAL COMPONENT DATA

Q25D-20 054038 Y7-54038 EATON ELECTRIC Pushbutton, black I, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: Q25D-20



Manufacturer	EATON - MOELLER
MPN / Reference	Q25D-20
Catalog number	Y7-54038
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-38AC0BFFE3
Generated	2026-08-04

Product Overview

Pushbutton, black I, momentary

Flush push-button 16 mm Return Black Inscription: I

Eaton Moeller® series RMQ16 Pushbutton, black I, momentary

Pushbutton, Product range: RMQ16, Single unit, Design: Flat, momentary, button plate: White, Button plate inscribed, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Pushbutton Catalog Number 054038 Model Code Q25D-20 EAN 4015080540380 Product Length/Depth 50 mm Product Height 25 mm Product Width 25 mm Product Weight 0.008 kg Certifications IEC/EN 60947-5

IEC/EN 60947

CSA File No.: 46552

CE

UL Category Control No.: NKCR

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

UL File No.: E29184

UL
UL 508
VDE 0660
CSA Features & Functions
Bezel color Black Bezel material Plastic Design Flat Features Labelled Fitted with: Front ring Inscription Inscribed General
Degree of protection IP65
NEMA 1 Degree of protection (front side) NEMA 1
IP65 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 3600 Operations/h Product
category RMQ16 Size Front dimensions: 25 x 25 mm Type Pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic proofing Damp heat, constant, to
IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Actuator
Actuating force 4 N Actuator color White Actuator function Momentary
Spring-return Communication
Connection to SmartWire-DT No Design verification
Equipment he...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25D-20 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.