

INDUSTRIAL COMPONENT DATA

Q18D-BL 086384 Y7-86384 EATON ELECTRIC Pushbutton, blue, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: Q18D-BL



Manufacturer	EATON - MOELLER
MPN / Reference	Q18D-BL
Catalog number	Y7-86384
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-8523C4EAAF
Generated	2026-07-28

Product Overview

Pushbutton, blue, momentary

Flush button. 16 mm. 18x18 mm. Return. Blue

Pushbutton, Product range: RMQ16, Single unit, Design: Flat, momentary, button plate: Blue, Button plate Blank, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: 18 x 18

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, blue, momentaryPushbutton, Product range: RMQ16, Single unit, Design: Flat, momentary, button plate: Blue, Button plate Blank, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: 18 x 18

General specificationsProduct nameEaton Moeller® series RMQ16 PushbuttonPart

no.Q18D-BLEAN4015080863847Product Length/Depth50 millimetreProduct height18 millimetreProduct width18

millimetreProduct weight0.007 kilogramCertificationsUL Category Control No.: NKCR

IEC/EN 60947

UL

CE

VDE 0660

CSA File No.: 46552

CSA Class No.: 3211-03

IEC/EN 60947-5

CSA

UL 508

UL File No.: E29184

CSA-C22.2 No. 14-05Product TradenameRMQ16Product TypePushbuttonProduct Sub TypeNoneFeatures & FunctionsBezel colorBlackBezel materialPlasticDesignFlatFitted with:Front ringInscriptionBlankGeneral informationDegree of protectionNEMA 1

IP65Degree of protection (front side)NEMA 1

IP65Lifespan, mechanical3,000,000 OperationsOpening diameter16 mmOperating frequency3600 Operations/hProduct categoryRMQ16SizeFront dimensions: 18 x 18 mmTypePushbutton actuatorAmbient conditions, mechanicalMounting positionAs requiredShock resistance40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27Climatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max60 °CAmbient operating temperature (enclosed) - min-25 °CAmbient operating temperature (enclosed) - max40 °CClimatic proofingDam...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18D-BL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.