

INDUSTRIAL COMPONENT DATA

M22-D-S-X0 216609 Y7-216609 EATON ELECTRIC Pushbutton, flush, black 0, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22-D-S-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22-D-S-X0
Catalog number	Y7-216609
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-585433084F
Generated	2026-08-04

Product Overview

Pushbutton, flush, black 0, momentary

M22-D-S-X0

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Flat, momentary, black, inscribed, Bezel: titanium

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Flat, momentary, button plate: black, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216609 Model Code M22-D-S-X0 EAN 4015082166090 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.009 kg

Certifications CSA

CSA Class No.: 3211-03

UL 508

UL Category Control No.: NKCR

IEC/EN 60947-5

UL

UL File No.: E29184

CSA File No.: 012528

CSA-C22.2 No. 14-05

CE

CSA-C22.2 No. 94-91

VDE 0660

IEC/EN 60947

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Flat

Classical Features Labelled Fitted with: Front ring Inscription Inscribed General

Degree of protection IP67

IP69K

IP66

NEMA 3R

NEMA 12

NEMA 4X

NEMA 13 Degree of protection (front side) NEMA 4X

IP67/IP69K Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600

Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuating force 5 N A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-D-S-X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.