

INDUSTRIAL COMPONENT DATA

M22-DR-S 216613 Y7-216613 EATON ELECTRIC Pushbutton, flush, black, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DR-S



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DR-S
Catalog number	Y7-216613
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-C508E2452C
Generated	2026-08-04

Product Overview

Pushbutton, flush, black, maintained

M22-DR-S

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Flat, maintained, black, Blank, Bezel: titanium

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Flat, maintained, button plate: black, Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216613 Model Code M22-DR-S EAN

4015082166137 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.011 kg

Compliances CE Marked Certifications CSA Std. C22.2 No. 94-91

UL 508

EN 60947-5

CSA Std. C22.2 No. 14-05

IEC 60947-5

VDE

CSA

CSA Class No.: 3211-03

UL

UL File No.: E29184

CSA-C22.2 No. 94-91

VDE 0660

IEC/EN 60947

CSA File No.: 012528

CE

CSA-C22.2 No. 14-05

IEC/EN 60947-5

UL Category Control No.: NKCR

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Flat

Classical Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank

General

Degree of protection IP66

NEMA 3R

IP69K

NEMA 12

IP67

NEMA 4X

NEMA 13 Degree of protection (front side) IP67/IP69K

NEMA 4X Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800 Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DR-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.