

INDUSTRIAL COMPONENT DATA

M22S-D-B 216601 Y7-216601 EATON ELECTRIC Pushbutton, flush, blue, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-D-B



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-D-B
Catalog number	Y7-216601
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-7F371366CE
Generated	2026-08-01

Product Overview

Pushbutton, flush, blue, momentary

M22S-D-B

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Flat, momentary, Blue, Blank, Bezel: black

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Flat, momentary, button plate: Blue, Button plate Blank,

Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections,

Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216601 Model Code M22S-D-B EAN

4015082166014 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.009 kg

Compliances Bureau Veritas

GoST-R

CE Marked Certifications CSA Certified

CCC Marked

Lloyd's Register Certified

CSA-C22.2 No. 94-91

CE

UL
CSA
CSA Class No.: 3211-03
CSA-C22.2 No. 14-05
CSA File No.: 012528
UL Category Control No.: NKCR
VDE 0660
IEC/EN 60947
IEC/EN 60947-5
UL 508
UL File No.: E29184
DNV
GL
LR Catalog Notes Includes contact block mounting adapter. Features & Functions
Bezel color Black Bezel material Plastic Design Flat
Classical Fitted with: Front ring Illumination Non-illuminated Inscription Blank General
Degree of protection IP69K
NEMA 12
IP66
NEMA 4X
NEMA 3R
IP67
NEMA 13 Degree of protection (front side) IP67/IP69K
NEMA 4X Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h
Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-D-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.