

**INDUSTRIAL COMPONENT DATA**

# M22S-D-R-X0 216606 Y7-216606 EATON ELECTRIC

## Pushbutton, flush, red 0, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-D-R-X0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | M22S-D-R-X0                   |
| Catalog number  | Y7-216606                     |
| Category        | Front element for push button |
| Minimum order   | 10 Pcs                        |
| Document ID     | EO-0BC69FB27D                 |
| Generated       | 2026-08-04                    |

### Product Overview

Pushbutton, flush, red 0, momentary

M22S-D-R-X0

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Flat, momentary, red, inscribed, Bezel: black

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Flat, momentary, button plate: red, Button plate inscribed,

Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections,

Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216606 Model Code M22S-D-R-X0 EAN

4015082166069 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.009 kg

Certifications CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE

UL Category Control No.: NKCR

UL File No.: E29184

CSA

CSA Class No.: 3211-03

CSA File No.: 012528

UL

VDE 0660

IEC/EN 60947

IEC/EN 60947-5

UL 508

DNV

GL

LR

ETIM for 216606 Low-voltage industrial controls and switchgear (EC000221)

Feature Name

Feature Value

Colour button (EF000190)

Red

Number of command positions (EF001372)

1

Construction type lens (EF006253)

Round

Hole diameter (EF000079)

22.5 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Type of button (EF001546)

Flat

Suitable for lighting (EF001142)

No

With protective cover (EF005500)

No

Labelled (EF001537)

Yes

Switching function latching (EF007447)

No

Spring-return (EF001407)

Yes

With front ring (EF006014)

Yes

Material front ring (EF005972)

Plastic

Colour front ring (EF002429)

Black

Degree of protection (IP), front side (EF003118)

IP67/IP69K

Degree of protection (NEMA), front side (EF011961)

4X

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-D-R-X0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.