

INDUSTRIAL COMPONENT DATA

M22S-D-R 216595 Y7-216595 EATON ELECTRIC Pushbutton, flush, red, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-D-R



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-D-R
Catalog number	Y7-216595
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-A03E95CA34
Generated	2026-07-29

Product Overview

Pushbutton, flush, red, momentary

M22S-D-R

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Flat, momentary, red, Blank, Bezel: black

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Flat, momentary, button plate: red, Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216595 Model Code M22S-D-R EAN

4015082165956 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.009 kg

Certifications UL Category Control No.: NKCR

UL

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

CSA File No.: 012528

IEC/EN 60947

IEC/EN 60947-5

VDE 0660

CSA

CE

CSA-C22.2 No. 94-91

UL 508

UL File No.: E29184

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Flat

Classical Fitted with: Front ring Inscription Blank General

Degree of protection IP69K

NEMA 3R

NEMA 4X

NEMA 12

IP67

IP66

NEMA 13 Degree of protection (front side) IP67/IP69K

NEMA 4X Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h

Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuating force 5 N Actuator color Red Actuator....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-D-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.