

INDUSTRIAL COMPONENT DATA

M22-DH-S-X0 216659 Y7-216659 EATON ELECTRIC

Pushbutton, raised, black 0, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DH-S-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DH-S-X0
Catalog number	Y7-216659
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-F40C079E1F
Generated	2026-08-05

Product Overview

Pushbutton, raised, black 0, momentary

M22-DH-S-X0

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Extended, momentary, black, inscribed, Bezel: titanium

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Extended, momentary, button plate: black, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216659 Model Code M22-DH-S-X0 EAN 4015082166595 Product Length/Depth 30 mm Product Height 35 mm Product Width 30 mm Product Weight 0.012 kg

Certifications UL

UL 508

CSA File No.: 012528

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

IEC/EN 60947-5

UL Category Control No.: NKCR

CE

CSA Class No.: 3211-03

CSA

IEC/EN 60947

UL File No.: E29184

VDE 0660

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Color Black Design Extended

Classical Features Labelled Fitted with: Front ring Inscription Inscribed General

Degree of protection NEMA 13

IP66

NEMA 4X

NEMA 12

NEMA 3R

IP67

IP69K Degree of protection (front side) IP67/IP69K

NEMA 4X Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h

Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

-40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Act...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DH-S-X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.