

INDUSTRIAL COMPONENT DATA

M22S-DH-S-X0 216660 Y7-216660 EATON ELECTRIC

Pushbutton, raised, black 0, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DH-S-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DH-S-X0
Catalog number	Y7-216660
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-F495B13E7D
Generated	2026-08-05

Product Overview

Pushbutton, raised, black 0, momentary

M22S-DH-S-X0

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Extended, momentary, black, inscribed, Bezel: black
Pushbutton, Product range: RMQ-Titan, Single unit, Design: Extended, momentary, button plate: black, Button plate
inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ
connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216660 Model Code M22S-DH-S-X0 EAN
4015082166601 Product Length/Depth 30 mm Product Height 35 mm Product Width 30 mm Product Weight 0.012 kg

Certifications CE

CSA

VDE 0660

UL File No.: E29184

CSA Class No.: 3211-03

UL

UL 508

UL Category Control No.: NKCR
CSA-C22.2 No. 94-91
CSA-C22.2 No. 14-05
IEC/EN 60947
IEC/EN 60947-5
CSA File No.: 012528
DNV
GL
LR Features & Functions
Bezel color Black Bezel material Plastic Design Extended
Classical Features Labelled Fitted with: Front ring Inscription Inscribed General
Degree of protection IP69K
IP67
NEMA 3R
NEMA 13
IP66
NEMA 4X
NEMA 12 Degree of protection (front side) NEMA 4X
IP67/IP69K Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600
Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient
conditions, mechanical
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min
-40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Communication
Connection to SmartWire-DT Yes
With SWD-RMQ connections Actuator
Actuating force 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DH-S-X0 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.