

INDUSTRIAL COMPONENT DATA

M22S-DRH-S 216664 Y7-216664 EATON ELECTRIC

Pushbutton, raised, black, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DRH-S



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DRH-S
Catalog number	Y7-216664
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-D1F5062562
Generated	2026-08-04

Product Overview

Pushbutton, raised, black, maintained

M22S-DRH-S

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Extended, maintained, black, Blank, Bezel: black

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Extended, maintained, button plate: black, Button plate Blank,

Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections,

Front dimensions: 22 x 22, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN

60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216664 Model Code M22S-DRH-S EAN

4015082166649 Product Length/Depth 30 mm Product Height 35 mm Product Width 30 mm Product Weight 0.013 kg

Certifications IEC/EN 60947-5

UL 508

CE

CSA Class No.: 3211-03

CSA

VDE 0660

CSA-C22.2 No. 94-91

IEC/EN 60947

UL

UL Category Control No.: NKCR

UL File No.: E29184

CSA File No.: 012528

CSA-C22.2 No. 14-05

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Extended

Classical Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank

General

Degree of protection IP67

NEMA 3R

NEMA 4X

NEMA 13

IP69K

NEMA 12

IP66 Degree of protection (front side) NEMA 4X

IP67/IP69K Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800 Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DRH-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.